

Aqualine Plus Fire Hose



Externally Elastomeric Coated, All Synthetic, EPDM Rubberlined Fire Hoses

CONSTRUCTION

Circularly woven jacket Coated with specially formulated Elastomeric RED Coating for protection against abrasion, mild chemicals and heat

INNER LINING

Ultra Light weight synthetic EPDM Rubber having low friction loss and very high ozone resistance.

CHARACTERISTICS

- Outer Coating of specially formulated RED POLYMER Resistant against abrasion, heat and mild chemicals
- Flexible – compact with small coil diameter
- Resistant to fungus, rot and mildew
- High Burst and Kink pressure ratings
- Colour : Red

APPLICATIONS


- Fire Brigades
 - Power Plants
 - Railways
 - High rise buildings
 - Steel Plants
 - Sailing Vessels
- and other industries

APPROVALS

- MED WHEELMARK approved under EN 14540
- Lloyd's approved to EN 14540 Type 2
- Conforming to BS 6391 Type 2
- CE APPROVED
- Manufactured under ISO 9001:2015 & ISO 45001:2018 quality systems
- ISI Marked IS 636 : 2018 Type 2

Nominal Size (in)	Working Pressure (psig)	Proof Pressure (psig)	Burst Pressure (psig)
1½" (38mm)*	260	320	650
1¾" (45mm)	260	320	650
2" (50mm)	260	320	650
2½" (63mm)*	260	320	650
2¾" (70mm)	260	320	650
3" (76mm)	260	320	650

AN ISO 9001 - 2015 COMPANY



CHHATARIYA FIRETECH INDUSTRIES

23A SURYODAYA MILLS COMPOUND | 96 TARDEO ROAD
MUMBAI 400 034 | INDIA
PH 91 22 23513705 / 23521313 / 23510849
E-MAIL chhatariya1@gmail.com

FACTORY :
89 GIDC ESTATE, MAHUVA 364 290, GUJARAT, INDIA
PH +91 2844 228887 / 228749
E-MAIL info@chhatariyafiretech.com